



Profile Premium

Liquid Compound



Product Description

Profile Premium Liquid Compound is a high performance, water-based cutting compound which removes P1200 or finer sanding marks from production gel coats and painted finishes, and is the perfect solution for restoring oxidised and weathered gel coat surfaces.

Great on dark colours, it delivers a high gloss finish and is used as a one step product on white gel coats and as the first stage of a two part compounding process where higher gloss and lower swirl is required.

Product Information

Size	Code	Ctn Qty
1 ltr	PRL101	6
1 US gallon	PRL106	2

Key Benefits

- | | |
|---|---|
| • Engineered for Production Gel Coats & Weathered Gel Coats | Removes P1200 or finer sanding marks |
| • Time & Money Saved | Quicker application and much less product required versus leading brands, so highly economical |
| • High Quality Abrasive | No haze, no die back |
| • Clean To Use | No clogging, extended wool pad life |
| • Reduced Heat Build Up | Product stays wet longer |



Use With

Machine Application




G Mop 8" Twisted Wool Pad - Single Sided
GMW801



G Mop 8" Twisted Wool Pad - Double Sided
GMW806



G Mop Yellow Compounding Foam
GMC312 (3" foam)
GMC612 (6" foam)
GMC812 (8" foam)



Farécla Finishing Cloth **FC-3** (3 x cloths)




G Mop Flexible Back Plate for 8" Pads
GMB814 (14mm thread)
GMB858 (5/8" thread)
GMB816 (16mm thread)




Adaptor for G Mop 8" Double Sided Wool Pad
GMA014 (14mm thread)
GMA058 (5/8" thread)
GMA016 (16mm thread)


How To Use




1 Sand area - Profile Premium Liquid Compound removes up to P1200



2 Attach G Mop 8" Single Sided Wool Pad to a polisher



3 Shake well and apply a small amount on to the pad and surface



4 Prime pad with product and compound at 1500 to 1800rpm



5 Wipe clean with a Finishing Cloth

*It is always recommended to test on an inconspicuous area prior to general use

Technical Information

Appearance: **White thick liquid**
Viscosity: **High viscosity**
VOC Content: **266g/L**
Relative Density: **1.15**
pH: **7 - 8**
Paint Type Compliance: **Marine gel coats, wood, aerospace, caravans & motorhomes etc.**

Additional Information

Clean applicators before and after use with a Spurring Brush to prevent dried product damaging the surface being worked on.



Spurring Brush
1090005

